

# Introduction

"We appreciate your purchase of the Eversolo Play Music Streaming Amplifier."

Play is a high-performance, fully-featured Hi-Res music streaming integrated amplifier. As a digital audio player.

Play not only excels at playing and managing various high-resolution local music Nes, but also incorporates premium third-party HI-Res atreaming services including TIDAL, Gobuz, HGERESAUDIO, Amazon Masic, WebDAY, URINP and more. As an interroted another order supports Optical, Cossial, HDMI ARC, sealed LINE IX, and PHONO (cost, Users can start

that maked to see about to assess the same

Additionally, Play supports USB sudio output, delivering up to DSD512 and PCM 768KHz/32bit sudio data.

The decoding section of Play utilizes the high-performance AK44935EQ DAC, which incorporates VELVET SOUND technology

designed to deliver extremely low distortion and noise (THD+N).

Play features an audio power amplifier capable of 60W/80 and 110W/40 output

It is advised to read this manual to make sure the product's features are applied correctly


# Product Specification

Product Sp	ecifications	
Body Material	Aluminium alloy	
Display	5.5° LCD Touchscreen	
DAC	AKH400EQ	
Storage	4G DDR4 +32G eMMC	
USB Ports	USB3.0*2	
Dhemet	FU-45(10/100/1000Mbps)	
WIFI	2.4G+5G	
DAC Decoding	Supports up to Stereo DSDS12, PCM 76890 iz 30888	
Music File Formats	DSD(DSF,DFF,SACD ISO Support DST up to DSDS12), MP3.APE.WW.FLAC.AF.AFF.AAC.APIG.CUE	
Music Services	TDAL, Gobur, HGHRESAUDIO, Ameron Music etc.	
Music Streaming	Roon Ready, TIDAL Connect, DLNA etc.	
Eluetooth Input	Bluetooth BTS.O, SBC/AAC	
HDMI ARC Input	Supports up to Stereo PCM 19290 tr 24881	
Optical/Coaxial Input	Supports up to Stereo PCM 19290-iz 24ER and DOP64	
Analog Line In	Maximum input voltage 2VFIVS	
PHONO Input	Supports MM/MC	
USB Audio Output	Supports up to Stereo DSD512 Native and PCM 75890 tr 3288 (Supports DAC audio devices with UAC standard only)	
Cossial Output	Supports up to Stereo PCM 19290 to 24881 and DCP64	
Subwooter Output	Adjustable crossover frequency from 40 Hz to 500 Hz	
Amplifier Output	60W/8D: TIOW/4D	
Control Methods	On-screen touch control, Android/Phone/Pad. AFP control	
Water Plant	Webs Inc	

# Technical Specifications

Continuous Output Power	60W RMSBIBD 110W RMSBI4D		
Amplifier Type	Class D Amplifier		
Amplifter Gain	20.848		
input Sensitivity	2V		
THD(20Hz-20Hz)	<0.0007% 5W at 1904z		
Signal-to-Noise Ratio(SNR)	>109:60, 60A-wt 40 120W		
Prequency Response	2014r-2010 tr < ±0.25dB 2014r-4010 tr < -3dB		
Damping Factor	>107		
Channel Crosstalk	<-108d8		
PHONO	Amplifier gain: MM 60dB MC 74dB Input sensitivity: MM 5mV MC 0.5mV BMA: 40.5dB 2014-20044		

# Hardware



### Power on/ot

er in: Connects to front-end devices (such as source or preamp) for

synchronized wake-up. The trigger voltage is 5V-12V.

3 JARC: Connects to TVs, projectors, or other display devices with HCMI eARC/ARC

4.Optical input: Connects CD players, set-top boxes, digital transport

5 Cossial Input: Connects CD players, set-top boxes, digital transport 6 Cossed Terminal: Connects to ground wire of digital transport

7 JUNE IN (RCA): Connects to preemplifiers to transfer analog signal

PHIONO MM/MC: Connects to turnishies
 PReset Port: For system reset or OTG firmware updates

Gigabit Ethernet network socket
 USB 3.0 OTG: Connects to external storage devices/optical disc drives/PC

USB (Audio out): USB audio output for connecting audio devices (DAC)

13 .Sub Out: Connects to subvooter

14 SPEAKER Output: Connects to L/R channel speakers

\* LISB maximum marks current 25. If connection asternal crains due observe classes

JSB maximum supply current: 2A. If connecting external optical disc drivers, please use an additional power adapter or USB splitter cable (USB OTG and USB AUDIO OUT).

# Front Panel

1 Display Screen: LCD toucheon

2. Volume Knob/Power Switch: For adjusting volume level and power on/off

\* Turn the volume level to the minimum level before use (default volume -20x5)

# Left Panel (CD Edition Only)



# Knob



Volume Control: The knob can be turned clockwise to turn up the volume and

## Power On/Off



Peace and have the least once to term it on when the desire is necessari off

Standar Clink to immediately not the portion into standay mode. Tirred standard Sourcel times are evaluable for choosing, or you can customize one

# Basic Operation

# Home Screen



Function enfrance: Displays Music Services, Functions, Apps, Connect, Cloud, Settings,

# Music Plauer



## Description

Favorite: Add the currently playing track to My Favorites

Play Queue: A list of all tracks currently selected to be played, such as all tracks by a certain



Course Colombian



# Music Septon

Music Services: Includes Music Library, Lister at Will My Payorites, attenuative services.





## Music Service Usane

Music Services: Includes Music Library, Listen at Will, My Favorites, streaming services, and music spore. Loo in your account to play music from third-party agos and

Note: \* More result services will be explicite for described places therein the official

# Function

Options: Files, CD, EQ, Room Correction, Multi room, and Transfer song.



## File Manager

The File Manager manages files in local storage and removable storage devices, and supports LAN access to NFG and SMIII services. It allows file operations (copy, paste,



## CD Playback & Ripping

By connecting with a USB CD-ROM, the device can both play music from CD and rip music

ties from CD.

CD ripping instructions: Navigate to Trunctions > CD ripping\*, and plok > 2 to start CD.



Click\* &\*to change the path for saving music files to local storage, removable storage, and NESC/SMI devices in LAN.



Note: The device supports WAV and FLAC for ripping files.





## Note

The PEQ function sucrks for the internal player and digital audio inputs (coasial/optical/ARC), also supports analog signal input captured through a high-spec AD tup to 1920 to, then output via distril audio interfaces or speaker interfaces.

# Room Correction





\*Please scan the code to check the guide





ENNYTHIN "These scan the code to check the gus

## Transfer

Access "Functions > Transfer" to transfer songs from computer to this device according the description. Make sure computer and the device are on the same network, choose





## Anns

can view, initials and unminitial strict-party apple. To install strict-party apple, thestly foods the APK file and copy it to a removable hand drive, insert the hand drive into this is and find APK file in Tille Manager, then install it by one click.

# Note: \* It is recommended to install tablets apps GVGCROLO



# Muela Connect











# eversol o









# Settings

Settings: Source, Audio Settings, Playback Settings, Display Settings, Network Settings,

Make Dor clinital outstands for a 1900 SDDSD and the universe to requirement his universe.

# minned o

## Audio Settings

Αυ	dio Settings	(8)
(2)	Speaker output	
<u> </u>	Subwooter	[3
0	COAX output	D
	USB DAC output	Ω
8	ARC mode ARC	9
13	Phono in made MC	a
rie.	Maximum volume had	

Navigate to "Settings > Playback Settings" to configure Playback Mode, CD Auto Play, Gapless playback, ReplayGain source mode, Auto-play Queue on Startup, and Auto Ope



### y Settings

screensaver modes, knob brightness & color, VU meter display modes, spectrum,

Someon Brightness: Adjust the brightness level of the device screen.

Knob Settings: Customize the brightness and color of the knob light.

Someonsee: Enable the system to enter someon saver mode after inactivity.

Dit by pressing the power button or touching the screen recreases ModescChoose from 9 preset screen saver styles. I MeterSelect different VU meters according to personal preference.

Dis	play Settings	
0	Knob settings	
Ö	Screen brightness	
00	There	Simple 3
0	Screenwer	
0	VU meter	VU meter 1 - 2
the	Spectrum	
Œ	Play Details	
83	Automatically hide ravigation bar	



# Thems Next are to "Settings > Display Settings > Thems" to switch between "Simple" and "Class thems.



# Network Settings

Diversolo play supports control via a mobile app. Navigate to "Settings > Phone Contracts the GR code to download and install "Diversolo Control" app.

scan the UH code to download and intra "burnion Control" app.
Alternatively, download the app from the official website or the manual.



# Mobile Controlling App

e the device and phone are on the same local network. Open the app, select device of "plan" to add the device. Once connected, you will access the control interface.



Android (mobile phone) and ICIS (mobile phone or tablet) apps are supported.

Scan the GR code in the Quick Start Guide for download.

# Other Settings

Language

Navigate to "Settings > Other Settings > Language" to choose menu langua



# USB OTG Part

The USB-OTG port can be used to connect with computer by a USB data cable, so that it is convenient to copy and manage local files.



Access "Settings > Update". Online update and USB update are suppo



### ---

Connect to the internet, navigate to "Settings > Update" or "Settings > A

select "Chiline update," and follow prompts. Wall for automatic restart.

USB update

Download the firmware update package from the official website to a USB stick.

### restort.

Note:

\* Don't remove the USB stick or power off during the upgrade process.

# Connection and Setting

connection and Setting

## USB OLITRUT

Use a USB audio cable to connect the device's USB audio output to the external DAC's USB



Note:

# LIST mode output managers on to PSPSTS history and DPM SSSS in 1999.

Coastal Output

Use a Cossolal audio cable to connect the Cossolal output of this device to the input of an audio decoder or Al/ receiver.



Note: Coaxial output supports up to Stereo PCM 1929-tz 24Bit and DOP64

### peaker Output

Hed spasser terminals (positive) → Connect to the positive (+) terminals of your speakers.

Elack speaker terminals (negative) → Connect to the negative (-) terminals of your speakers.



Note:
The positive and regative terminals of the left and right channels on the output port must correspond to the speaker's positive and regative terminals respectively.

This device supports connecting a subwooter using a duel-ended red and white RCA cable. Neighbor to Settings > Source > Culput port > Subwooter, and turn on the Sub ON/OFF button.



### .

This device supports connecting a front-end equipment with S/FDIF output (e.g., media player or CD player) using an Optical or Cosolal audio cable.

Sections to Matthew Microral and select Matter left or Microrial left



Notes: \* Please use 75 Chm Cossial audio cable for Cossial connection

Please use standard optical audio cable for Optical connection.

### ....

ice supports connecting a TV, projector, or other display device with HDAM. RC functionality using an HDM cable.Navigate to "Settings > Source" and



(Support HESS AMIC/III

Notes: \* Please connect to the HDM input port on the TV labeled as ARC or eARC.

\* Please use a physical HDMI cable for the connection, not an optical HDMI cable

### LIME IN

This service support connecting to element such sources with arrang HLA such (e.g., CD players) using a dual-ended red and white RCA cable.



PHONO Input

viernal turnitable using a dual-ended red and white car', select "THONO In" .

switch PHONO input mode, revigate to "Settings > Audio Settings > PHONO in mode".



### liuetooth Input

This device has a built-in Blastooth audio receiver module that supports lossiess audioprotocols auch as SEC/AVC, allowing it so function as a high-quality Blastooth decoder. Pair it with mobile, Avicans for wheleas Blastooth playsock, Avigates for Settings > Source then select 'Blastooth In'. On your mobile device, enable Blastooth, search for the device

Note: \* Illustooth reception format depends on transmitting device. Normally Android

# Downloads

# For product ferrogen upgrade, USB other and mobile control AFE down

the Downloads page on official website and scan QR code.

These varieties excluse effective developments the object double click the less his and text-





....

### pecial Note:

in order to improve the user experience, Everacio will update firmware from time to time. Therefore, this product manual may differ from the actual setting menus of the product.

## Safety Warning

Uso water splashing or dripping, do not put objects with liquid like vase on the device.

2.It is Class I device, there must be organized measures inside the box when using