


Hisense

Hisense floor stand manual


(Please read this manual carefully before use and keep it properly)

Go Tech, and Beyond


Packing List




Retractable Rod x 1



Universal Gimbal x 1



Quick Installation Plate x 1




Quick Installation Fixture x 1



Quick Installation Screw x 1

Instruction Manual x 1




Base x 1


Product specification

Items	Parameters
Product Name	Hisense Floor Stand
Adjustable Height	580mm~950mm (±5mm)
Base Diameter	300mm±0.5mm
Gimbal Maximum Weight Load	< 7kg
Net Weight	5.2kg±0.05kg
Sections of Retractable Rod	Two-section
Color	Tarnish


Instructions For Assembling and Usage




① Take out the Retractable Rod and link it to the base;




② Take out the Universal Gimbal and install it to the top of the Retractable Rod;




③ Rotate the screw switch of the Retractable Rod to the right;




④ Hold the Retractable Rod and pull it up to a suitable height;



⑤ Fix the Quick Installation Fixture on the Universal Gimbal;



⑥ Use the Quick Installation Screw to lock the Quick Installation Plate on the projector;



⑦ Install the projector with the Quick Installation Plate on the Quick Installation Fixture.

Product Maintenance and Precautions

Cleanup and Maintenance:

- Do not use a metal brush to clean this product.
- Please use a soft and lint-free cloth dampened with mild soapy water or neutral dishwashing detergent (diluted with water) to wipe gently.

Precautions:

- Do not install projections exceeding the maximum weight on the floor stand to avoid property damage and personal injury.
- Do not touch or move the product easily when it is in working condition to avoid property damage and personal injury.
- Do not scratch the surface of the product with sharp objects to avoid damage on the surface.
- Do not clean the product with acidic or alkaline lotion to avoid surface corrosion.

Note: This product is only suitable for projectors with standard 1/4 screw holes on the bottom.

HISENSE VISUAL TECHNOLOGY CO.,LTD

NO.218 QIANWANGANG ROAD,ECONOMY&TECHNOLOGY

DEVELOPMENT ZONE,QINGDAO,CHINA

MADE IN CHINA